




Standardprofiler




L- Profil (liksidig)					
A ≤ 3mm 6060 F22-T6 (EN-AW-6060) Yt- klass 6					
A > 3mm 6082-T6 (EN-AW-6082) Yt- klass 6					
5-meters längder					
	B-C	A		B-C	A
	12	2		40	5
	15	1,5		50	3
	15	2		50	5
	20	2		60	6
	20	3		80	8
	25	2			
	25	3			
				Neutralanodiserad 10µm	
	30	3		12	2
	30	5		15	2
	35	3		20	2
	40	4		25	2
	40	2		30	3




L- Profil (oliksidig)							
A ≤ 3mm 6060 F22-T6 (EN-AW-6060) Yt- klass 6							
A > 3mm 6082-T6 (EN-AW-6082) Yt- klass 6							
5-meters längder							
	B	C	A		B	C	A
	15	10	2		100	50	3
	20	10	2		100	50	5
	20	15	2		130	65	10
	30	20	3				
					Neutralanodiserad 10µm		
	40	20	2		15	10	2
	40	25	3		20	10	2
	50	25	2		20	15	2
	50	30	4		30	20	3
	60	40	3		40	20	2
	60	40	5		50	25	2
	80	50	6		100	50	3




U- Profil									
A ≤ 3mm 6060 F22-T6 (EN-AW-6063) Yt- klass 6									
A > 3mm 6082-T6 (EN-AW-6082) Yt- klass 6									
5-meters längder									
	B	C	A ¹	A ²		B	C	A ¹	A ²
	8	8	1	1		60	40	5	5
	10	10	1,5	2		80	40	5	5
	12	12	2	2		100	50	5	5
	15	15	2	2		120	60	5	5
	18	18	2	2					
	20	10	2	2					
						Neutralanodiserad 10µm			
	20	20	2	2		8	8	1	1
	25	15	2	2		10	10	1,5	2
	25	25	3	3		12,5	11,5	2	2
	30	20	3	3		15	15	2	2
	30	30	3	3		18	18	2	2
	40	25	3	3		20	10	2	2
	50	30	4	2		20	20	2	2



T- Profil			
A ≤ 3mm 6060 F22-T6 (EN-AW-6060) Yt- klass 6			
A > 3mm 6082-T6 (EN-AW-6082) Yt- klass 6			
5-meters längder $A^2=A^1$,			
B	C	$A^1 - A^2$	
20	20	2	
30	30	3	
40	40	4	
50	50	5	
60	60	6	




I- Profil				
A ≤ 3mm 6060 F22-T6 (EN-AW-6060) Yt- klass 6				
A > 3mm 6082-T6 (EN-AW-6082) Yt- klass 6				
5-meters längder				
B	C	A ¹	A ²	
8,8	20	1,2	2	
100	50	5	5	
Neutralanodiserad 10µm				
8,8	20	1,2	2	




Z- Profil			
6060- F22-T6 (EN-AW-6060 F22) Yt- klass 6			
$C^2=C^1, A^2=A^1$, 6,6-meters längder			
B	$C^1 - C^2$	$A^1 - A^2$	
7	15	1	
23	30	3	
35	20	2	

Profilerna finns även i:
H, C, W och Z- special
 samt systemprofiler mm


Standard rör



Runda rör									
6060 F22-T6 (EN-AW-6060 F22)									
Yt- klass 5/5-meters längder									
	D	d	A		D	d	A		
	8	6	1		50	46	2		
	10	8	1		54	50	2		
	12	10	1		60	54	3		
	16	13	1,5		90	80	5		
	19	16	1,5		100	90	5		
	20	17	1		100	96	2		
	22	19	1,5		110	104	3		
	25	21	2		120	110	5		
	25	22	1,5	Neutralanodiserad 10µm					
	28	25	1,5						
	30	26	2		10	8	1		
	31	28	1,5		12	10	1		
	35	31	2		16	13	1,5		
	40	34	3		22,5	19,5	1,5		
	45	41	2		25	22	1,5		



Kvadratiska rör							
6060 F22-T6 (AN-AW-6060 F22)							
Yt- klass 5/5-meters längder							
	B	A		B	A		
	10	1		45	2		
	12	1		50	2,5		
	15	1		70	2		
	20	1,5	Neutralanodiserad 10µm				
	20	2					
	20	2					
	25	1,5		20	2		
	25	2		25	1,5		
	30	1,5		25	2		
	30	2		30	2		
	35	2		40	2		
	40	2		50	2,5		



Rektangulära rör											
6063-T6 (EN-AW-6063)											
Yt- klass 5/5-meters längder											
	B	C	A ¹	A ²		B	C	A ¹	A ²		
	20	10	1,5	1,5		100	35	3	2,5		
	25	15	2	2		100	40	2,5	2,5		
	30	20	2	2		100	50	3	3		
	35	17	2	2		120	40	2,5	2,5		
	40	25	2	2		120	50	3	3		
	50	30	2	2	Neutralanodiserad 10µm						
	50	30	2,5	2,5							
	60	40	2,5	2,5		40	25	2	2		
	80	40	2,5	2,5		50	30	2	2		
	100	18,5	2,5	2		60	40	2,5	2,5		